

P7200 Series Felt Tape:

Synthetic Felt, 100% Polyester with High Performance Acrylic Adhesive on One Side.

FEATURES and BENEFITS: • Felt with a High Performance Acrylic Adhesive for Durable and Long Lasting Bond • Available in Tape Rolls, Die Cut Shapes, Sheets, Long Length Spools, and Master Log Rolls.

Material:	Synthetic Felt, 100% Polyester	note:
Pres-On Material Category:	Felt	-
Color:	White	visual
Texture:	Felt	-
Shape:	Roll - Strip - Die Cut Gasket	-
Material Technical Data	Result	test / note:
Weight (material)	.12"T - 1 lbs/yd2, .18"T - 1.25 lbs/yd2, .25"T -1.5 lbs/yd2	(without PSA / liner / film)
Temperature High	325° F	-
Temperature High Constant	300° F	-
ASTM Standard	Accordance with ASTM Standards for Evaluating Non-Woven Textiles	-
Sizes	available options:	stock code / note:
Thickness:	1/8"	12
Thickness:	3/16"	18
Thickness:	1/4"	25
Length:	Standard Roll & Custom Lengths	-
Spooling:	available	Continuous Length
Width:	Any roll width up to full 54" log rolls	-
Die Cuts:	available	Kiss-Cut, Kits, Separate, Drawings
Sheets:	any size up to 50" wide	-
Adhesive	Type / Rating	note:
Standard Adhesive:	Acrylic, Permanent	Direct Coat (wet coat)
Adhesive Outdoor Rating	Excellent	
Adhesive Shelf Life	2 Years	room temperature, relative humidity
Filter	none	Mylar available for die-cuts
No Adhesive (special option)	available	-

Color and Finish may vary based on production lot. Measurement tolerances vary based on thickness and width, contact Pres-On for specific tolerance to your finished product.

APPLICATION NOTES: Ensure bonding surfaces are well unified, clean, dry, and free of dirt and oils. Apply firm and even pressure to improve adhesive-to-surface contact. Allow proper temperature and time to enhance bond strength. It is the end user's responsibility to determine final suitability of Pres-On's product for use in their application.

 For Terms and Conditions: visit <https://www.preson.com/terms-conditions/>

Adhering to a higher standard™