



## P7300 SERIES

### P7300 Series Felt Tape:

Decorative Felt, Synthetic, PET with High Performance Acrylic Adhesive on One Side.

**FEATURES and BENEFITS:** • A decorative needle punched felt used for furniture or other applications that requires a good appearance, a High-Tack Rubber Adhesive for great bond • Available in Tape Rolls, Die Cut Shapes, Sheets, Long Length Spools, and Master Log Rolls.

<b>Material:</b>	<b>Decorative Felt, material: PET</b>	<b>note:</b>
Pres-On Material Category:	Felt – Needle Punched	-
Color:	White, Black, Gray, Brown, Special (check availability)	visual
Texture:	Felt	-
Shape:	Roll - Strip - Die Cut Gasket	-
<b>Material Technical Data</b>	<b>Result</b>	<b>test / note:</b>
Weight (material)	.06" T - 0.31 lbs/yd <sup>2</sup> .12" T – 0.75 lbs/yd <sup>2</sup>	(without PSA / liner / film)
Temperature High	325° F	-
Temperature High Constant	300° F	-
ASTM Standard	Accordance with ASTM Standards for Evaluating Non-Woven Textiles	-
<b>Sizes</b>	<b>available options:</b>	<b>stock code / note:</b>
Thickness:	1/16"	06
Thickness:	1/8"	12
Length:	1/16" thickness = 1005' standard 1/8" thickness = 75' stander *Special lengths available	-
Spooling:	available	Continuous Length
Width:	Any roll width up to full 54" log rolls (~50" useable)	-
Die Cuts:	available	Kiss-Cut, Kits, Separate, Drawings
Sheets:	any size up to 50" wide	-
<b>Adhesive</b>	<b>Type / Rating</b>	<b>note:</b>
Standard Adhesive:	Rubber, High Tack & Permanent	Direct Coat (wet coat)
Adhesive Shelf Life	1 Years	room temperature, relative humidity
No Adhesive (special option)	Available as plain (no adhesive)	-

Color and Finish may vary based on production lot. Measurement tolerances vary based on thickness and width, contact Pres-On for specific tolerance to your finished product.

**APPLICATION NOTES:** Ensure bonding surfaces are well unified, clean, dry, and free of dirt and oils. Apply firm and even pressure to improve adhesive-to-surface contact. Allow proper temperature and time to enhance bond strength. It is the end user's responsibility to determine final suitability of Pres-On's product for use in their application.

For Terms and Conditions: visit <https://www.preson.com/terms-conditions/>

Adhering to a higher standard™

Find the right product for your application today! Call Pres-On at 800-323-7467.  
visit [www.preson.com](http://www.preson.com), or email [sales@preson.com](mailto:sales@preson.com).

  
2600 E. 107<sup>th</sup> Street | Bolingbrook, IL 60440  
630-628-2255 | [www.preson.com](http://www.preson.com)